

Standard Projector

RICOH PJ WX5462 PJ HD5452



RICOH
imagine. change.

Great value. High quality. Perfect for you.

Gain the clarity you need in your presentations with these great value, high-quality RICOH PJ WX5462 and PJ HD5452 projectors thanks to display options of WXGA and HD. Straight-forward installation, easy-to-adjust functions, the 1.36x zoom, vertical lens shift and 4-corner correction abilities all make for efficient and seamless projection. You'll also benefit from flexible connectivity with two HDMI ports – one supports MHL. Perfect presentations every time for your business or education facility.

- 4,100 / 3,800 lumens brightness
- 4,000 hours (native) / 10,000 hours (eco mode) of lamp life
- Compact and easily portable design
- Flexible installation and easy projection with vertical and horizontal keystone, vertical lens shift, four-corner adjustment, geometric correction and 1.36x zoom
- Easy content sharing from smart devices with HDMI/MHL connectivity
- Compatibility with device management systems like Crestron, AMX® Device Discovery, Extron and PLink (Class 1) via network

Main specifications

Key features	PJ WX5462	PJ HD5452
Type	Standard	Standard
Projection system	DLP	DLP
Resolution	WXGA (1,280 x 800 pixels)	1080p (1,920 x 1,080 pixels)
Panel size	0.65 inches	0.65 inches
Brightness	4,100 lumens	3,800 lumens
Contrast ratio	2,000:1 — Standard	1,800:1 — Standard
	8,000:1 — High Contrast Mode	8,000:1 — High Contrast Mode
Zoom ratio	1.36x	1.36x
Throw ratio	1.113 – 1.523:1	1.06 – 1.45:1
Projection distance	1.3 – 7.2 m	1.3 – 7.2 m
Projection size	40 – 300 inches	41 – 307 inches
Lens focal length	15.98 – 21.42 mm	15.98 – 21.42 mm
Lens aperture (F-stop)	2.5 – 2.93	2.5 – 2.93
Speaker	10 W mono	10 W mono
Lamp type	High-pressure mercury	High-pressure mercury
Lamp life	4,000 hours (Standard Mode), 10,000 hours (Eco Mode)	4,000 hours (Standard Mode), 10,000 hours (Eco Mode)
Interfaces	Computer In, Computer Out, Video In, S-Video In, HDMI1/MHL In, HDMI 2 In, LAN, Audio 1 In, Audio 2 In, Audio Out, USB micro B (for firmware updates), PC-Control (RS232C)	Computer In, Computer Out, Video In, S-Video In, HDMI1/MHL In, HDMI 2 In, LAN, Audio 1 In, Audio 2 In, Audio Out, USB micro B (for firmware updates), PC-Control (RS232C)
3D support	DLP Link	DLP Link
Maximum power consumption	360 W	360 W
Dimensions (W x D x H)	314.2 x 223.5 x 91.8 mm — without protrusion	314.2 x 223.5 x 91.8 mm — without protrusion
	314.2 x 223.5 x 105.3 mm — with protrusion	314.2 x 223.5 x 105.3 mm — with protrusion
Weight	Approximately 3.2 kg	Approximately 3.2 kg

RICOH
imagine. change.

www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD

30 Cecil Street, #13-01/08 Prudential Tower, Singapore 049712

Phone: +65 6830 5888, Fax: +65 6830 5830

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2021 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.