

**A4 Colour Printer and MFP** 

# RICOH SP C360DNw SP C360SFNw







### A compact workhorse for the busy workplace

The SP C360DNw and SP C360SFNw are LED printers that combine quality, speed and reliability with modern workflow capabilities, making them ideal for small to medium businesses and small workgroups.

Featuring an easy-to-use setup wizard and convenient WIFI connectivity, the models are easy to install, ensuring that you can start using the wide range of productivity features on offer, such as double-sided scanning, almost instantly to save time and boost productivity.

Both models offer advanced security with Locked Print to protect confidential documents from unauthorised viewing. Additionally, these printers are eco-friendly with low typical electricity consumption (TEC) values and minimal power consumption in Sleep Mode.

- The SP C360DNw comes with a tiltable 4-line LCD panel for easy viewing and navigation.
- The SP C360SFNw comes with an intuitive 7" Smart Operation Panel, which provides both ease-ofuse and opens up a world of additional functionality.

## Working smart has never been simpler

### Speed and clarity meets light and compact

- These LED printers can print 1,200 dpi quality documents at 600 dpi speed, enabling you to produce sharper and higher quality documents in a shorter amount of time.
- Because LED technology uses less components to print, these printers are smaller and lighter, making them suitable for a variety of businesses and small spaces.
- Fast print speeds of up to 30ppm and quick first print time of 7.2 seconds (Black and White) and 8.6 seconds (Full Colour) translates into high productivity.

#### Functionality at your fingertips

- Intuitive operating concept with the tiltable 4-line LCD Display (SP C360DNw) offers an at-a-glance view of useful functions such as network and remaining toner status.
- The 7" touch panel interface (SP C360SFNw) provides you with a full touch screen experience and variety of applications that help you in your business.
- Single Pass Document Feeder with ID card copy/scan functionality allows fast double-sided scanning.

### Security and Ease of use

- Both the SP C360DNw / SP C360SFNw come with a set-up wizard that cuts out the need to navigate complex processes.
- Convenient wireless connectivity enables you to set up and use the printers with "Plug & Play-like" simplicity.
- Protect confidential documents from unauthorised viewing with Locked Print, which requires you to enter a password on the operation panel before printing.

#### **Seamless Connectivity**

- Print on the go from your smart devices phone, tablet, and notebook with AirPrint<sup>®</sup>, Mopria<sup>®</sup> and RICOH Smart Device Connector.
- Print directly from USB using the built-in slots without the need to use a computer.
- Gain quick access to the printers via the embedded NFC tag or tap on WIFI Direct without connecting to the corporate network.









#### RICOH SP C360DNw / SP C360SFNw

MAIN SPECIFICATIONS

lodel	SP C360DNw	SP C360SFNw	
unction	Print	Print / Scan / Copy / Fax	
eneral			
onfiguration		Desktop	
echnology		LED	
anel	4-Line LCD Display	7" Smart Operation Panel	
uplex		Automatic	
imension	400 x 515 x 360 mm	420 x 540 x 547 mm	
/eight	32.0kg	41.5kg	
rocessor		1.2GHz	
lemory	Standard: 512MB Max: 512MB	Standard: 2GB Max: 2GB	
	Standard: Wireless LAN (IEEE	Standard: Wireless LAN (IEEE	
	802.11a/b/g/n), Ethernet 10 base-	802.11a/b/g/n), Ethernet 10 base-	
nterface	T/100 base-TX/1000 base-T, USB 2.0,	T/100 base-TX/1000 base-T, USB 2.0,	
	USB 2.0 Host, USB 2.0-Device	USB 2.0 Host, USB 2.0-Device, SD slot	
1obile Capability	RICOH Smart Device Co	onnector, Mopria <sup>®</sup> , Apple AirPrint <sup>®</sup> , NFC	
ower Consumption (Max)		1.2kW	
eady Mode	34.5w	43.6w	
nergy Saver (Sleep)	0.78w	1.5w	
EC Value	1.2 kWh	1.3 kWh	
ower Source		20-240V, 50/60 Hz	
	2	Certified	
nergy Star		Certified	
int	E	n (A4 Simpley) 28ppm (A4 Dupley)	
int Speed (A4)	B/W· 30ppr	n (A4 Simplex) 28ppm (A4 Duplex) A4 Simplex) 28ppm (A4 Duplex)	
arm Up time	20 seconds	25.1 seconds	
rst Print Out Time		8.6 seconds, B/W: 7.2 seconds	
int Resolution		•	
		600 x 600 dpi, 600 x 1,200 dpi equivalent, 600 x 2,400 dpi equivalent, 1,200 x 1,200 dpi	
int Language	Standard: PCL5c, PCL6, PostScript 3 (Emulation), PDF direct (Emulation) PCL/PostScript 3 (Emulation): 80 Roman fonts + 13 international fonts		
nts	PCL/PostScript 3 (Emulatio		
etwork Protocol		TCP / IP	
'indows <sup>®</sup> environments	Windows <sup>®</sup> Vista, Windows <sup>®</sup> 7, Windows <sup>®</sup> 8.1, Windows <sup>®</sup> 10, Windows <sup>®</sup> Server 2008, Windows <sup>®</sup> Server 2008R2, Windows <sup>®</sup> Server 2012, Windows <sup>®</sup> Server 2012R2, Windows <sup>®</sup> Server 2016		
Andows environments			
lac OS environments	Mac OS X v.10.9 or later		
NIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX, Citrix XenDesktop 7.0/7.1, Citrix XenApp 6.5/7.5		
AP® R/3® environments	SAP <sup>®</sup> R/3 <sup>®</sup> , SAP <sup>®</sup> R/4 <sup>®</sup>		
ther Supported environments	AS/400 <sup>®</sup> using OS/400 Host PrintTransform, IBM iSeries		
opy			
opy Speed (A4)		Up to 30cpm	
ocument Feeder Type	-	Single Pass Document Feeder	
ocument Feeder Capacity	-	50 Sheets	
esolution	-	Flatbed: 600 x 600 dpi SPDF: 1,200 x 1,200 dpi	
Initials Com			
Iultiple Copy	· · ·	up to 999	
eduction / Enlargement	-	From 25% to 400% in 1% steps	
opy Features	-	Image density adjustment (Manual only 9 levels), Copy mode (Text / PI Text Photo / Lighten Background), Memory copy, Duplex copy, Combine (2 in 1), ID Card Copy, Auto Tray Switch, Directional Size Magnificat Auto Start, User Program, Electronic Sorting, Image Rotation, Series Copy (2 sided -> 1 sided 2 sheets)	
can			
an Speed	-	Full colour: 20ipm (Max) , B/W: 30ipm (Max)	
esolution	-	Standard: 100 - 600 dpi	
		Default: 200 dpi	
iginal Size	-	A4	
ndled Drivers		Network TWAIN	
an To	-	E-mail, Folder, USB, SD card, SMB	
ĸ			
rcuit		PSTN, PBX	
mpatibility	-	ITU-T (CCITT) G3	
solution		8 x 3.85 line/mm, 200 x 100 dpi, 8 x 7.7 line/mm, 200 x 200 dpi	
mpression Method	-	MH, MR, MMR	
ansmission Speed	-	G3: 3 second(s) (200 x 100 dpi)	
odem Speed		Max: 33.6 Kbps	
an Page Per Minute		28 pages per minute	
emory Backup	-	Yes	
per Handling			
commended Paper Size	A4, B5, A5, B6, A6, Legal, Letter, HLT, Executive, F, Foo	olscap, Folio, 16K, Custom size: (Min) 82.5mm x 148mm (3.25" x 5.83"),	
		ım x 356mm (8.50" x 14.01")	
per Input Capacity		s, Bypass: 100 sheets, Max: 850 sheets	
per Output Capacity	Maximum: 200 sheets	Maximum: 150 sheets	
per Weight	Pape	r tray(s): 56 - 220 g/m² ass tray: 56 - 220 g/m²	
	Вура	ass tray: 56 - 220 g/m²	
otions			
cessories	Paper Feed Unit TK1230 (250	sheets), Paper Feed Unit TK1240 (500 sheets)	
onsumables			
ner cartridges (C/M/Y/K) (Regular Yield)	Black: Approx 2,500 pages	C/M/Y: Approx 1,500 pages	
ner cartridges (C/M/Y/K) (High Yield)	Black: Approx 7,000 pages	C/M/Y: Approx 5,000 pages	
	Black: Approx 15,000 pages	C/M/Y: Approx 12,000 pages	
notoconductor unit			
otoconductor unit nsumable yield measuring method ISO/IEC 19798	Black. Approx 15,000 pages		



#### www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD

103 Penang Road #08-01/07, VISIONCREST Commercial, Singapore 238467 Phone: +65 6830 5888, Fax: +65 6830 5830

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2020 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.





